

# ISO L21549/11 tapered roller bearings

ISO L21549/11 tapered roller bearings Needs Analysis , Manufacturing Service . Get 32 mm A1 Your Free. 60 mm A

|   |          |
|---|----------|
| A   | 60 mm    |
| A1  | 32 mm    |
| B   | 41.2 mm  |
| d   | 41.28 mm |
| Dz  | 95 mm    |
| E   | 25 mm    |
| G   | M6x1     |
| H   | 54.2 mm  |
| H1  | 13 mm    |
| H2  | 108 mm   |
| J   | 90 mm    |
| L   | 120 mm   |
| L1  | 42 mm    |
| N   | M14      |
| s1  | 20.6 mm  |
| S   | 10.2 mm  |
| Z   | 70.2 mm  |
| C   | 31.85 kN |
| C0  | 20.8 kN  |
| T min.                                      | -20 °C   |
| T max.                                      | 200 °C   |
| Weight                                      | 2.32 kg  |
| Recommended tightening torque for set screw | 8 Nm     |

|                                 |               |
|---------------------------------|---------------|
| Designation of housing          | PA209N-       |
| Designation of bearing          | US209-26G2T20 |
| Designation of closed end cover | SCC209        |
| Designation of open end cover   | SCOU209-26    |