

# ISO L555233/10 tapered roller bearings

Shop ISO L555233/10 tapered roller bearings huge online discount inventory. and Import machinery parts your car needs with 17 mm d Free Shipping and Free 12 mm B Extended Warranty.

d	17 mm
D	40 mm
B	12 mm
d1	24.1 mm
D1	34.9 mm
a min	1.9 mm
a max	2.06 mm
Ca min	2.92 mm
Ca max	3.18 mm
rs min	0.6 mm
rNs min	0.5 mm
D3 max	38.1 mm
b min	1.35 mm
b max	1.65 mm
r0 max	0.4 mm
D4 max	44.6 mm
f	1.07 mm
Snap ring reference	R40
Radial clearance class	CN
Mass	0.07 kg
Dynamic load, C	9.4 kN
Static load, C0	4.75 kN

Fatigue limit load, $C_u$	0.22 kN
$f_0$	13.1
$N_{ref}$	18,000 rpm
$N_{lim}$	24,000 rpm
Min operating temperature, $T_{min}$	-20 °C
Max operating temperature, $T_{max}$	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	3.99 Hz
Characteristic outer ring frequency, BPF0	3.05 Hz
Characteristic inner ring frequency, BRFI	4.95 Hz
$d_{a \min}$	21 mm
$d_{a \max}$	24.1 mm
$D_{a \max}$	36 mm
$r_{a \max}$	0.6 mm
$r_{Na \max}$	0.5 mm
$D_b \min$	45.5 mm