

ISO NA4930 needle roller bearings

Request A Quote For 22.0 Inventory Your Special ISO NA4930 needle roller bearings Needs Today! Free N/A Minimum Buy Quantity Quotes. ISO 9001 certified.

| | |
|---------------------------------|--|
| Inventory | 22.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight | 0.008 |
| EAN | 4547359551679 |
| Product Group | B00308 |
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C3-Loose |
| Inch – Metric | Metric |
| Long Description | 7MM Bore; 19MM Outside Diameter; 6MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 IS |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |

| | |
|------------------------------|----------------------------|
| Manufacturer Item Number | 607ZZC3/1K |
| Weight / LBS | 0.018 |
| D | 0.748 Inch 19 Millimeter |
| d | 0.276 Inch 7 Millimeter |
| Outer Race Width | 0.236 Inch 6 Millimeter |
| bore diameter: | 7 mm |
| static load capacity: | 910 N |
| outside diameter: | 19 mm |
| precision rating: | ISO Class 0 |
| overall width: | 6 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| bearing material: | High Carbon Chrome Steel |
| closure type: | Double Shielded |
| cage material: | Steel |
| row type & fill slot: | Single Row Non-Fill Slot |
| inner ring width: | 6 mm |
| snap ring included: | Without Snap Ring |
| outer ring width: | 6 mm |
| internal clearance: | C3 |
| maximum rpm (grease): | 34000 rpm |
| operating temperature range: | -40 to 120 °C |
| fillet radius: | 0.3 mm |
| dynamic load capacity: | 2240 N |
| manufacturer product page: | Click here |