

# ISO NA6907 needle roller bearings

We work closely with our ISO NA6907 needle roller bearings manufacturing partners 0.0 Inventory to bring the best value to customers.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 20.884   |
| EAN                       | 0883450010474  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22217  |
| Seals                     | Triple Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Heavy Duty  |
| Long Description          | 4 Bolt Pillow Block; 75MM Bore; 82.6MM Base to Center Height; Tapered Adapter Sleeve Mount; Spherica |

|                               |                               |
|-------------------------------|-------------------------------|
| UNSPSC                        | 31171511                      |
| Harmonized Tariff Code        | 8483.20.40.80                 |
| Noun                          | Bearing                       |
| Keyword String                | Pillow Block                  |
| Manufacturer Item Number      | DVPF17K075SEN                 |
| Weight / LBS                  | 51                            |
| Nominal Bolt Center to Center | 8.4 Inch   213 Millimeter     |
| Bolt Spacing Minimum          | 7.6 Inch   193.04Millimeter   |
| d                             | 2.953 Inch   75 Millimeter    |
| B                             | 3.252 Inch   82.6 Millimeter  |
| Bolt Spacing Maximum          | 9.1 Inch   231.14Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter          |
| D                             | 3.23 Inch   82.042 Millimeter |