

ISO NH2218 cylindrical roller bearings

ISO NH2218 cylindrical roller bearings SEARCH – Whether it's agriculture or construction equipment 190x240x50 Size (mm) your working on, Has the you need.

Size (mm)	190x240x50
Bore Diameter (mm)	190
Outer Diameter (mm)	240
Width (mm)	50
d	190 mm
F	210 mm
D	240 mm
B	50 mm
C	50 mm
r min.	1,5 mm
s	1,5 mm
da min.	198 mm
Da max.	232 mm
ra max.	1,5 mm
Weight	5,62 Kg
Basic dynamic load rating (C)	227 kN
Basic static load rating (C0)	680 kN
(Grease) Lubrication Speed	1 300 r/min
rs min	1.5 mm
s max	1.5 mm
Dw	7.5 mm
Lw	40 mm

Lubrication hole on outer ring	Oui/Yes
k	3.5 mm
Lubrication hole on inner ring	Non/No
Radial clearance class	CN
Precision class	P0
Mass	5.62 kg
Cr	227 kN
C0r	680 kN
Nlim (grease)	1,300 rpm
Nlim (oil)	1,900 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.48 Hz
Characteristic rolling element frequency, BSF	28.97 Hz
Characteristic outer ring frequency, BPF0	27.03 Hz
Characteristic inner ring frequency, BRFI	28.97 Hz
da min	198 mm
Da max	232 mm
ras max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	5.92
Product Group	B04144