

# ISO NJ18/750 cylindrical roller bearings

ISO NJ18/750 cylindrical roller bearings Warehouse offers car parts and car accessories. We sell discount online as 0.0 Inventory well as cheap machinery parts.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN                                      |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 7.718                                       |
| EAN                       | 0883450333207                               |
| Product Group             | M06288                                      |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar                           |
| Housing Style             | 4 Bolt Pillow Block                         |
| Rolling Element           | Spherical Roller Bearing                    |
| Housing Material          | Cast Steel                                  |
| Expansion / Non-expansion | Non-expansion                               |
| Mounting Bolts            | 5/8 Inch                                    |
| Relubricatable            | Yes   |
| Insert Part Number        | 22213                                       |
| Seals                     | Triple Lip Nitrile Rubber                   |
| Housing Configuration     | 1 Piece Solid                               |
| Inch – Metric             | Metric                                      |
| Other Features            | Double Row   Single Collar   With Set Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 4 Bolt Pillow Block; 60MM Bore;<br>70MM Base to Center Height;<br>Concentric Collar Mount;<br>Spherical Rolle |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Weight / LBS                  | 20  |
| d                             | 2.362 Inch   60 Millimeter  |
| Bolt Spacing Minimum          | 7.125 Inch   180.975Millimeter  |
| B                             | 2.756 Inch   70 Millimeter  |
| Nominal Bolt Center to Center | 7.9 Inch   199.5 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| D                             | 3.39 Inch   86.106 Millimeter   |
| Bolt Spacing Maximum          | 8.75 Inch   222.25Millimeter  |