

ISO NJ30/530 cylindrical roller bearings

320 Outer Diameter (mm) offers a ISO NJ30/530 cylindrical roller bearings selection of Genuine at Wholesale Prices. We are a ISO NJ30/530 cylindrical roller bearings Certified 440x320x56 Size (mm) Parts Retailer

Size (mm)	440x320x56
Bore Diameter (mm)	440
Outer Diameter (mm)	320
Width (mm)	56
d	320 mm
D	440 mm
B	56 mm
d1	357.68 mm
D1	402.83 mm
r1,2 – min.	3 mm
da – min.	333 mm
Da – max.	427 mm
ra – max.	2.5 mm
Basic dynamic load rating – C	276 kN
Basic static load rating – C0	400 kN
Fatigue load limit – Pu	8.6 kN
Reference speed	2800 r/min
Limiting speed	2400 r/min
Calculation factor – kr	0.02
Calculation factor – f0	16
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	34.331
EAN	7316577122117
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Brass
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	320MM Bore; 440MM Outside Diameter; 56MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61964 MA
Weight / LBS	66
Bore	12.598 Inch 320 Millimeter
Outer Race Width	2.205 Inch 56 Millimeter
Outside Diameter	17.323 Inch 440 Millimeter
bore diameter:	320 mm
static load capacity:	400 kN
outside diameter:	440 mm

finish/coating:	Uncoated
overall width:	56 mm
bearing material:	Steel
bore type:	Round
cage material:	Steel
closure type:	Open
fillet radius:	3 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	2800 rpm
snap ring included:	Without Snap Ring
series:	61
internal clearance:	C0
weight:	56.2 lbs
operating temperature range:	Max 250 °F
manufacturer product page:	Click here
dynamic load capacity:	276 kN
manufacturer upc number:	7316577122117
d1 ≈	357.68 mm
D1 ≈	402.83 mm
r1,2 min.	3 mm
da min.	333 mm
Da max.	427 mm
ra max.	2.5 mm
Basic dynamic load rating C	276 kN
Basic static load rating C0	400 kN
Fatigue load limit Pu	8.65 kN
Calculation factor kr	0.02
Calculation factor f0	16
Mass bearing	25.5 kg