

ISO NJ5217 cylindrical roller bearings

Online shopping ISO NJ5217 cylindrical roller bearings from a great selection 85x125x33.1 Size (mm) at Store. ... Accessories.

Size (mm)	85x125x33.1
Bore Diameter (mm)	85
Outer Diameter (mm)	125
Width (mm)	33,1
d	85 mm
D	125 mm
T	33,1 mm
d1	125 mm
r min.	1 mm
A	52 mm
D1	88 mm
R	100 mm
da min.	109 mm
Da max.	101 mm
ra max.	1 mm
Weight	1,35 Kg
Basic dynamic load rating (C)	96 kN
Basic static load rating (C0)	264 kN
(Grease) Lubrication Speed	1600 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.57

EAN	0029176029608
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Aligning Seat
Long Description	85MM Bore 1; 88MM Bore 2; 125MM Outside Diameter; 33MM Height; Ball Bearing; Single Direction; Not B
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	53217
Weight / LBS	2.97624
Outside Diameter	4.921 Inch 125 Millimeter
Bore 2	3.465 Inch 88 Millimeter
Bore 1	3.346 Inch 85 Millimeter
Height	1.299 Inch 33 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
bore diameter:	85 mm
static load capacity:	59500 lbf

outside diameter:	125 mm
dynamic load capacity:	21600 lbf
overall width:	37 mm
operating temperature range:	Maximum of +120 °C
thrust bearing type:	Single-Direction
maximum rpm:	2400 rpm
outside diameter design:	Straight
cage material:	Steel Cage
separable or banded:	Separable
fillet radius:	1 mm
race type:	Flat
series:	52300
precision rating:	ABEC1, P0
SRI	7.7
hidYobi	53217
LangID	1
D_	125
SREX	0.065
C	96
B_	33.1
hidTable	ecat_NSSDTB
Oil rpm	2400
SRE	7.7
mass	1.35
GRS rpm	1600
ra	1
SRIX	0.065
D_a	101
SRIN	0

C0	264
SREN	0
D_1	88
Prod_Type3	TB_SD_WAS
da	109
DA_	14.288
Z_	21
yobi	53217
A_	52
T3	33.1
SDM_	105
r	1
KBRG	5121
R_	100