

ISO NKXR 25 Z complex bearings

ISO NKXR 25 Z complex bearings with easy-to-use parts graphics, giving you the ability to check parts 5x19x6 Size (mm) 19 Outer Diameter (mm) availability, pricing, examine remanufactured options.

| | |
|----------------------------------------|---------|
| Size (mm) | 5x19x6 |
| Bore Diameter (mm) | 5 |
| Outer Diameter (mm) | 19 |
| Width (mm) | 6 |
| Bearing Type | Sealed |
| Bore Dia (d) | 5.0000 |
| Outer Dia (D) | 19.0000 |
| Width (B) | 6.0000 |
| Radius (min) (rs) | 0.300 |
| Dynamic Load Rating (Cr) | 1,986 |
| Static Load Rating (Cor) | 717 |
| Max Speed (Grease) (X1000 RPM) | 32 |
| Max Speed (Oil) (X1000 RPM) | 40 |
| Max. Shaft Shoulder Dia. Inner (Ui) | 8.5 |
| Min. Housing Shoulder Dia., Outer (Uo) | 16.500 |
| Ball Qty | 6 |
| Ball Dia (Dw) | 3.5000 |
| Weight (g) | 8.89 |
| Precision | A1 |
| Standard Clearance | K25 |

| | |
|----------|-----------------------------|
| Material | Martensitic Stainless Steel |
|----------|-----------------------------|