

ISO NNCF5024 V cylindrical roller bearings

ISO NNCF5024 V cylindrical roller bearings 630x780x88 Size (mm) 780 Outer Diameter (mm) Needs 630 Bore Diameter (mm) Analysis , Manufacturing Service . Get Your Free.

| | |
|---------------------|------------|
| Size (mm) | 630x780x88 |
| Bore Diameter (mm) | 630 |
| Outer Diameter (mm) | 780 |
| Width (mm) | 88 |
| d | 630 mm |
| D | 780 mm |
| B | 88 mm |
| C | 88 mm |
| d1 | 680 mm |
| r1 min. | 4 mm |
| r2 min. | 4 mm |
| r3 min. | 4 mm |
| r4 min. | 4 mm |
| D1 | 728 mm |
| E | 739 mm |
| da min. | 645 mm |
| Da max. | 765 mm |
| das rec. | 674 mm |
| ra max. | 3 mm |
| rb max. | 3 mm |
| S | 8 mm |
| Db max | 765 mm |

| | |
|-------------------------------|-----------|
| Weight | 92,5 Kg |
| Basic dynamic load rating (C) | 1870 kN |
| Basic static load rating (C0) | 5000 kN |
| Fatigue load limit (Pu) | 390 |
| Reference speed | 300 r/min |
| Limiting speed | 360 r/min |