

# ISO NNCL4832 V cylindrical roller bearings

Offer High Quality Brand ISO NNCL4832 V cylindrical roller bearings .Contact Us 110 mm d Online to Get Best Quote.

|   |           |
|---|-----------|
| d   | 110 mm    |
| D   | 240 mm    |
| B   | 50 mm     |
| d2  | 150.2 mm  |
| D1  | 202.7 mm  |
| rs min  | 3 mm      |
| Number of lubrication holes                   | 4         |
| b   | 9 mm      |
| k   | 5 mm      |
| e   | 0.21      |
| Y1  | 3.2       |
| Y2  | 4.77      |
| Y0  | 3.13      |
| Radial clearance class                        | C3        |
| Dynamic load, C                               | 495 kN    |
| Static load, C0                               | 615 kN    |
| Fatigue limit load, Cu                        | 116 kN    |
| Nref  | 2,800 rpm |
| Nlim  | 3,500 rpm |
| Min operating temperature, Tmin               | -40 °C    |
| Max operating temperature, Tmax               | 120 °C    |
| Characteristic cage frequency, FTF            | 0.42 Hz   |
| Characteristic rolling element frequency, BSF | 5.83 Hz   |

|   |               |
|---|---------------|
| Characteristic outer ring frequency, BPF0 | 6.68 Hz       |
| Characteristic inner ring frequency, BRFI | 9.32 Hz       |
| da min                                    | 124 mm        |
| Da max                                    | 226 mm        |
| ra max                                    | 2.5 mm        |
| Inventory                                 | 0.0           |
| Manufacturer Name                         | NTN           |
| Minimum Buy Quantity                      | N/A           |
| Weight / Kilogram                         | 11.56         |
| EAN                                       | 4547359261301 |
| Product Group                             | B04311        |