ISO NNU6020 cylindrical roller bearings

ISO NNU6020 cylindrical roller bearings 0.0 Inventory SEARCH — Whether it's agriculture or construction equipment your working N/A Minimum Buy Quantity on, Has the you need.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	4.77
EAN	7316576674129
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	22210
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch — Metric	Inch
Other Features	Double Row Heavy Duty Open End With Grub Screw

Long Description	2 Bolt Pillow Block; 1-15/16" Bore; 2-1/4" Base to Center Height; Stepped Sleeve Mount; Sp
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SYE 1.15/16 N
Weight / LBS	10.5
d	1.938 Inch 49.225 Millimeter
Actual Bolt Center to Center	0 Inch OMillimeter
Bolt Spacing Maximum	7.25 Inch 184.15Millimeter
D	2.343 Inch 59.5 Millimeter
Nominal Bolt Center to Center	6.6 Inch 167 Millimeter
В	2.25 Inch 57.15 Millimeter
Bolt Spacing Minimum	6.75 Inch 171.45Millimeter
bore diameter:	1.9375 in
bolt center-to-center length:	7 in
overall length:	8.8750 in
base width:	2-1/2 in
overall height:	4.5000 in
expansion type:	Expansion Bearing (Floating)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard
bore type:	Round
radial dynamic load capacity:	21600 lbf
housing construction:	Solid Pillow Block

radial static load capacity:	22400 lbf
base to bore centerline:	2.5000 in
maximum rpm:	2150 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYE
locking device:	Concentric Collar
replacement bearing:	22210