

ISO NP2222 cylindrical roller bearings

ISO NP2222 cylindrical roller bearings SKF Manufacturer Name SEARCH – Whether it's agriculture or N/A Minimum Buy Quantity construction equipment your working on, 0.0 Inventory Has the you need.

| | |
|------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.254 |
| EAN | 7316577722058 |
| Product Group | B04144 |
| Roller Surface Profile | Flat |
| Profile | Yoke Type |
| Enclosure | Sealed |
| Rolling Element | Cylindrical Roller Bearing – Double Row |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Full Complement With Flanged Inner Ring Labyrinth Seal |
| Long Description | 20MM Bore; 47MM Roller Diameter; 24MM Roller Width; Flat Roller; Yoke Type; Sealed; Cylindrical Roll |
| UNSPSC | 31171530 |
| Harmonized Tariff Code | 8482.50.00.00 |

| | |
|-------------------------------|----------------------------|
| Noun | Bearing |
| Keyword String | Cam Follower |
| Manufacturer Item Number | NUTR 20 X |
| Weight / LBS | 0.551 |
| Roller Diameter | 1.85 Inch 47 Millimeter |
| Roller Width | 0.945 Inch 24 Millimeter |
| d | 20 mm |
| roller diameter: | 47 mm |
| radial dynamic load capacity: | 28.6 kN |
| roller width: | 24 mm |
| radial static load capacity: | 33.5 kN |
| bore diameter: | 20 mm |
| roller material: | Steel |
| roller shape: | Flat |
| maximum rpm: | 3800 rpm |
| bearing element: | Cylindrical Rollers |
| finish/coating: | Uncoated |
| overall width: | 25 mm |
| manufacturer catalog: | Click here |
| closure type: | Sealed |
| series: | NUTR |
| operating temperature range: | 300 °F |
| manufacturer upc number: | 7316577722058 |
| D | 47 mm |
| C | 24 mm |
| B | 25 mm |
| d1 | 27 mm |
| r1,2 min. | 1 mm |
| r, r3,4 min. | 0.5 mm |

| | |
|---|------------|
| Basic dynamic load rating C | 28.6 kN |
| Basic static load rating C ₀ | 33.5 kN |
| Fatigue load limit P _u | 3.9 kN |
| Maximum dynamic radial loads F _r max. | 17.6 kN |
| Maximum static radial loads F _{0r} max. | 25 kN |
| Limiting speed | 3800 r/min |
| Mass support roller | 0.24 kg |