

ISO NUP29/500 cylindrical roller bearings

What is the best 85x120x23 Size (mm) place to buy ISO NUP29/500 cylindrical roller bearings online? Manufacturing Service . 85 Bore Diameter (mm) 120 Outer Diameter (mm)

| | |
|-------------------------------|-----------|
| Size (mm) | 85x120x23 |
| Bore Diameter (mm) | 85 |
| Outer Diameter (mm) | 120 |
| Width (mm) | 23 |
| d | 85 mm |
| D | 120 mm |
| T | 23 mm |
| B | 23 mm |
| C | 18 mm |
| a | 21,2 mm |
| r min. | 1,5 mm |
| r2 min. | 1,5 mm |
| da min. | 93,5 mm |
| da max | 93 mm |
| Da min | 109 mm |
| Da max. | 111,5 mm |
| Db min. | 115 mm |
| ra max. | 1,5 mm |
| rb max. | 1,5 mm |
| Weight | 0,794 Kg |
| Basic dynamic load rating (C) | 97,1 kN |
| Basic static load rating (C0) | 165 kN |

| | |
|--------------------------------------|------------|
| (Grease) Lubrication Speed | 2900 r/min |
| (Oil) Lubrication Speed | 3900 r/min |
| Calculation factor (e) | 0,33 |
| Calculation factor (Y ₀) | 1,01 |
| Bearing No. | 32917JR |
| r(min) | 1.5 |
| r ₁ (min) | 1.5 |
| Cr | 122 |
| C ₀ r | 165 |
| Cu | 25.0 |
| Grease lub. | 2900 |
| Oil lub. | 3900 |
| a(mm) | 21.2 |
| d _a (min) | 93.5 |
| d _b (max) | 93 |
| D _a (max) | 111.5 |
| D _a (min) | 109 |
| D _b (min) | 115 |
| S _a (min) | 5 |
| S _b (min) | 5 |
| r _a (max) | 1.5 |
| r _b (max) | 1.5 |
| e | 0.33 |
| Y ₁ | 1.83 |
| Y ₀ | 1.01 |
| (Refer.) Mass (kg) | 0.794 |