

# ISO SL182980 cylindrical roller bearings

ISO SL182980 cylindrical roller bearings Industries and Applications ? We sell discount online as 0.0 Inventory well as cheap machinery REXNORD Manufacturer Name parts.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 2.59  |
| EAN                       | 0662327121877   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | YG228E3L  |
| Seals                     | Triple Lip Contact  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Single Row   Standard Duty   Standard Backing   Wide Inner Race |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-3/4" Bore; 2-1/8" Base to Center Height; Eccentric Collar Mount; Ba |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | P3Y228E3   |
| Manufacturer Internal Number  | 5812187  |
| Weight / LBS                  | 5.7  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter   |
| d                             | 1.75 Inch   44.45 Millimeter   |
| D                             | 2.219 Inch   56.363 Millimeter   |
| Actual Bolt Center to Center  | 5.6 Inch   143Millimeter   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter   |
| Nominal Bolt Center to Center | 5.6 Inch   142.5 Millimeter  |
| B                             | 2.125 Inch   53.98 Millimeter  |