

ISO UCP306 bearing units

ISO UCP306 bearing units Deal is your source for OEM N/A Minimum Buy Quantity and accessories. We sell 0.0 Inventory Genuine at discount prices.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	11.705
EAN	7316576657313
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH3224A (Specify bore)
Withdrawal Nut	KM27
Inch – Metric	Metric
Long Description	120MM Tapered Bore; 215MM Outside Diameter; 76MM Width; C0-Medium Clearance; Adapter Mount; Double R
Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available

UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	25.781
B	76 mm
Adapter Part Number	SNW124 H2324 HA2324 HE2324 (Specify Bore) Inch H2324 (Specify bore) Millimeter
d	120 mm
D	215 mm
bore diameter:	120 mm
maximum rpm:	2800 RPM
outside diameter:	215 mm
operating temperature range:	Maximum of +390 °F
overall width:	76 mm
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	76 mm
dynamic load capacity:	695 kN
fillet radius:	2 mm

static load capacity:	930 kN
series:	232
d2 ≈	141 mm
D1 ≈	182 mm
b	8.3 mm
K	4.5 mm
r1,2 min.	2.1 mm
Da max.	203 mm
ra max.	2 mm
Basic dynamic load rating C	732 kN
Basic static load rating C0	930 kN
Fatigue load limit Pu	93 kN
Reference speed	2000 r/min
Limiting speed	2800 r/min
Calculation factor e	0.35
Calculation factor Y1	1.9
Calculation factor Y2	2.9
Calculation factor Y0	1.8
Mass bearing	11.5 kg