

JNS NAF 153212 needle roller bearings

What is the best place 70x125x24 Size (mm) to buy JNS NAF 153212 needle roller bearings online? Manufacturing Service .

Size (mm)	70x125x24
Bore Diameter (mm)	70
Outer Diameter (mm)	125
Width (mm)	24
d	70 mm
D	125 mm
B	24 mm
C	24 mm
Angle (α)	40 °
a	29.0 mm
r min.	1.5 mm
r1 min.	1 mm
da min.	79 mm
Da max.	116 mm
ra max.	1.5 mm
Weight	1.12 Kg
Basic dynamic load rating (C)	71,5 kN
Basic static load rating (C0)	59,5 kN
(Grease) Lubrication Speed	4300 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	1.121

EAN	4991893844344
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	70MM Bore; 125MM Outside Diameter; 24MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7214 B BNLS
Weight / LBS	2.47
Outside Diameter	4.921 Inch 125 Millimeter
Width	0.945 Inch 24 Millimeter
Bore	2.756 Inch 70 Millimeter
Configuration	Single Row
Bore Type	Cylindrical Bore
Bore Size	70 mm

Fillet Radius/Chamfer	1.5 mm
r1	1 mm
Dynamic Load Rating	71,500 N
Static Load Rating	59,500 N
Limiting Speed – Grease	4,300 rpm
Limiting Speed – Oil	5,600 rpm
da1 (min)	79 mm
da2 (min)	75 mm
Da1 (max)	116 mm
Da2 (max)	119.6 mm
ra (max)	1.5 mm
ra1 (max)	1 mm