JNS NKI 42/30 needle roller bearings

JNS NKI 42/30 needle roller bearings Engineering Calculator , Manufacturing Service . Get Your Free. 2.4375 in d

d2.4375 inbase width:3.1250 inoverall length:11.2500 inexpansion type:Non-Expansion Bearing (Fixed)overall height:6.1250 infinish/coating:Uncoatedmounting:Four-Bolt BaseB4.0000 inbearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISOlocking device:Double Set Screew		
overall length:11.2500 inexpansion type:Non-Expansion Bearing (Fixed)overall height:6.1250 infinish/coating:Uncoatedmounting:Four-Bolt BaseB4.0000 inbearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	d	2.4375 in
expansion type:Non-Expansion Bearing (Fixed)overall height:6.1250 infinish/coating:Uncoatedmounting:Four-Bolt BaseB4.0000 inbearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Split Pillow Blockoperating temperature range:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	base width:	3.1250 in
overall height:6.1250 infinish/coating:Uncoatedmounting:Four-Bolt BaseB4.0000 inbearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	overall length:	11.2500 in
finish/coating:Uncoatedmounting:Four-Bolt BaseB4.0000 inbearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	expansion type:	Non-Expansion Bearing (Fixed)
mounting:Four-Bolt BaseB4.0000 inbearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	overall height:	6.1250 in
B4.0000 inbearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	finish/coating:	Uncoated
bearing type:Tapered Rollerseal type:Felt Sealbore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	mounting:	Four-Bolt Base
seal type:Felt Sealbore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	В	4.0000 in
bore type:Roundlubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	bearing type:	Tapered Roller
lubrication type:Lubrication Fittinghousing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	seal type:	Felt Seal
housing construction:Split Pillow Blockoperating temperature range:Max 250°base to bore centerline:3.2500 inbolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	bore type:	Round
operating temperature range: Max 250° base to bore centerline: 3.2500 in bolt size: .5000 in duty type: Standard Duty series: RPBXT housing material: Cast Iron standards met: ABMA, ISO	lubrication type:	Lubrication Fitting
base to bore centerline: 3.2500 in bolt size: .5000 in duty type: Standard Duty series: RPBXT housing material: Cast Iron standards met: ABMA, ISO	housing construction:	Split Pillow Block
bolt size:.5000 induty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	operating temperature range:	Max 250°
duty type:Standard Dutyseries:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	base to bore centerline:	3.2500 in
series:RPBXThousing material:Cast Ironstandards met:ABMA, ISO	bolt size:	.5000 in
housing material: Cast Iron standards met: ABMA, ISO	duty type:	Standard Duty
standards met: ABMA, ISO	series:	RPBXT
, 	housing material:	Cast Iron
locking device: Double Set Screw	standards met:	ABMA, ISO
	locking device:	Double Set Screw
replacement bearing: RCI-207	replacement bearing:	RCI-207
D 8.6250 to 9.6250 in	D	8.6250 to 9.6250 in