

# JNS RNA 5916 needle roller bearings

How do you find the JNS RNA 5916 needle roller bearings specification? 53.975 mm da Manufacturers Online Free check

|                         |               |
|-------------------------|---------------|
| da                      | 53.975 mm     |
| Da                      | 140 mm        |
| Ca                      | 57.785 mm     |
| A1                      | 88.9 mm       |
| A2                      | 134.938 mm    |
| ba                      | 32.544 mm     |
| H                       | 167.481 mm    |
| H1                      | 88.9 mm       |
| H2                      | 31.75 mm      |
| J min.                  | 244.475 mm    |
| J max.                  | 279.4 mm      |
| L                       | 330.2 mm      |
| N1                      | 22.225 mm     |
| R1                      | 53.181 mm     |
| R2                      | 21.431 mm     |
| RG                      | 3/8 NPT       |
| PG                      | 1/8 NPT       |
| h                       | 36.513 mm     |
| Housing                 | SAF 613       |
| Bearing                 | 1313 EKTN9    |
| Adapter sleeve assembly | SNW 113×2.1/8 |
| Stabilizing ring        | 2 x SR-1613   |
| Labyrinth ring          | 2 x LOR 31    |

|  |                |
|--|----------------|
| PosiTrac Plus contact element          | 2 x B10724-32  |
| End plug (suffix Y)                    | EPR 7          |
| Max. speed for PosiTrac Plus seal      | 2600 r/min     |
| P60°                                   | 83.2 kN        |
| P90°                                   | 49.8 kN        |
| P120°                                  | 30.2 kN        |
| P150°                                  | 26.7 kN        |
| P180°                                  | 31.6 kN        |
| Pa                                     | 6.49 kN        |
| Mass pillow block                      | 17.1 kg        |
| Cap bolt                               | 2 x 5/8-11 UNC |
| Cap bolt recommended tightening torque | 298.3 N·m      |
| Cap bolt, SAE grade                    | 8              |
| Appropriate attachment bolt size G     | 0.75 in        |
| Initial grease fill                    | 175.77 g       |