

# KBC 25577/25523 tapered roller bearings

KBC 25577/25523 tapered roller bearings Product Brochures , N/A Minimum Buy Quantity Manufacturing Service . Get Your Free. 0.0 Inventory NSK Manufacturer Name

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | NSK  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9  |
| EAN                       | 0029176088278  |
| Product Group             | B04311   |
| Internal Clearance        | C0-Medium  |
| Mounting Method           | Shaft Mount  |
| Rolling Element           | Spherical Roller Bearing   |
| Bore Profile              | Straight   |
| Cage Material             | Bronze   |
| Enclosure                 | Open   |
| Number of Rows of Rollers | Double Row   |
| Relubricatable            | Yes  |
| Withdrawal Sleeve         | Not Applicable   |
| Inch – Metric             | Metric   |
| Long Description          | 120MM Straight Bore; 215MM Outside Diameter; 58MM Width; C0-Medium Clearance; Shaft Mount; Double Ro |
| UNSPSC                    | 31171510   |
| Harmonized Tariff Code    | 84823080   |
| Noun                      | Bearing  |

|                              |   |
|------------------------------|---|
| Keyword String               | Spherical                                       |
| Manufacturer Item Number     | 22224CAME4                                      |
| Weight / LBS                 | 9.06  |
| B                            | 2.283 Inch   58 Millimeter                      |
| d                            | 4.724 Inch   120 Millimeter                     |
| D                            | 8.465 Inch   215 Millimeter                     |
| Adapter Part Number          | Not Applicable Inch   Not Applicable Millimeter |
| bore diameter:               | 120 mm  |
| maximum rpm:                 | 3000 RPM  |
| outside diameter:            | 215 mm  |
| operating temperature range: | Maximum of +200 °C                              |
| overall width:               | 58 mm   |
| cage material:               | Brass   |
| bore type:                   | Straight  |
| bearing material:            | Steel   |
| outer ring type:             | Not Split                                       |
| cage type:                   | Inner Ring Guided                               |
| internal clearance:          | C0  |
| precision rating:            | RBEC 1 (ISO Class Normal)                       |
| closure type:                | Open  |
| finish/coating:              | Uncoated  |
| lubrication hole type:       | Lubrication Groove & Hole                       |
| outer ring width:            | 58 mm   |
| dynamic load capacity:       | 685000 N  |
| fillet radius:               | 2.1 mm  |
| static load capacity:        | 765000 N  |
| series:                      | 222   |