

KOYO 22226RHRK spherical roller bearings

LET OUR KOYO 22226RHRK spherical roller bearings 62 mm D EXPERTS GET YOU 25 mm d THE PARTS YOU NEED. 17 mm B

d	25 mm
D	62 mm
B	17 mm
rs min	1.1 mm
Radial clearance class	C3
Mass	0.23 kg
Dynamic load, C	21.2 kN
Static load, C0	10.9 kN
Fatigue limit load, Cu	0.5 kN
f0	12.6
Nlim (grease)	12,000 rpm
Min operating temperature, Tmin	-10 °C
Max operating temperature, Tmax	165 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.66 Hz
Characteristic outer ring frequency, BPF0	2.61 Hz
Characteristic inner ring frequency, BRFI	4.39 Hz
da min	31.5 mm
da max	35 mm
Da max	55.5 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.216
Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 3 ISO P6
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Steel
Rolling Element	Ball Bearing
Enclosure Type	Light Contact Seal
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row Deep Groove C3 Clearance Prelubricant
Long Description	25MM Bore; 62MM Outside Diameter; 17MM Width; 2 Seals Enclosure; ABEC 3 ISO P6 Precision; Steel Ba
UNSPSC	31171502
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball Deep Groove
Width	0.669 Inch 17 Millimeter
Bore	0.984 Inch 25 Millimeter

Outside Diameter	2.441 Inch 62 Millimeter
------------------	----------------------------