

KOYO 239/630R spherical roller bearings

What is the best 3-11/16 in Shaft Size place to buy KOYO 239/630R spherical roller bearings online? Manufacturing Service Mounted Bearing Engineering Group .

| | |
|-------------------------|-------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 3-11/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QVF22V311SB |
| Locking Style | Single V-Lock |
| Weight | 55 lb |
| Housing Style | Four-Bolt Square Flange |
| UPC Code | 0883450091695 |
| Dimension BC | 10.96 in |
| Dimension C | 5.5 in |
| Dimension D | 8.820 in |
| Dimension E | 7.75 in |
| Dimension F | 9.97 in |
| Dimension H | 1.50 in |
| Dimension J (Bolt Size) | 0.875 in |
| Dimension L | 4.49 in |
| Dimension L Exp | 4.57 in |
| Dimension L Fix | 4.49 in |
| Dimension N | 4.060 in |
| Dimension RV | 0.36 in |
| Dimension SV | 4.13 in |
| C0 – Static Load | 147000 lb |

| | |
|-------------------------------------|-----------|
| C – Dynamic Load (Basic) | 125000 lb |
| e – Geometry Factor | 0.26 |
| Y1 – Geometry Factor | 2.55 |
| Y2 – Geometry Factor | 3.80 |
| Oil Lubrication – M/N Seal | 900 rpm |
| Oil Lubrication – T Seal | 1700 rpm |
| Oil Lubrication – B/C/O Seal | 600 rpm |
| Grease Lubrication – M/N Seal | 900 rpm |
| Grease Lubrication – T Seal | 1200 rpm |
| Grease Lubrication – B/C/O Seal | 600 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0030 in |
| Eng Internal Radial Clearance – Min | 0.0053 |
| Eng Internal Radial Clearance – Max | 0.0067 |
| Pre Install Clearance Min | 0.0043 in |
| Pre Install Clearance Max | 0.0055 in |