

KOYO 2788AR/2735X tapered roller bearings

Find the discount KOYO 2788AR/2735X tapered roller bearings online 32,5 mm S1 you need . We offer 35 Bore Diameter (mm) ... If you check out our large selection of KOYO 2788AR/2735X tapered roller bearings once .

Bore Diameter (mm)	35
d	35 mm
S1	32,5 mm
Thread (Q)	Rp1/8
d3	51 mm
A	45 mm
A1	27 mm
B1	51,3 mm
H	47,6 mm
H1	19 mm
H2	93 mm
J	126 mm
L	163 mm
N	14 mm
N1	21 mm
Weight	1,6 Kg
Basic dynamic load rating (C)	25,5 kN
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A

Weight / Kilogram	1.6
EAN	4012802798357
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Relubricatable	Yes
Insert Part Number	GE35KLLHB
Seals	Double Non Contact Labyrinth
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Single Row Spherical Standard Shaft Height Extended Inner Race With Set Screw
Long Description	2 Bolt Pillow Block; 35MM Bore; 47.6MM Base to Center Height; Eccentric Collar Mount; Ball Bearing;
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	LASE35N
Weight / LBS	3.749
Bolt Spacing Minimum	4.807 Inch 122.1Millimeter
Base to Center Height	1.874 Inch 47.6 Millimeter

Length Thru Bore	2.012 Inch 51.1 Millimeter
Nominal Bolt Center to Center	5 Inch 127 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Maximum	5.429 Inch 137.9Millimeter
Bore	1.378 Inch 35 Millimeter