

KOYO 303/32CR tapered roller bearings

KOYO 303/32CR tapered roller bearings Deal is 88.9 mm da your source for OEM and accessories. We sell Genuine at discount prices.

da	88.9 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	152.797 mm
S	4.763 mm
ba	44.45 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
L	387.35 mm
N1	25.4 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	42.069 mm
Housing	SAF 520
Bearing	22220 EK
Adapter sleeve assembly	SNW 20×3.1/2

Stabilizing ring	SR-20-17
Labyrinth ring	2 x LOR 103
End plug (suffix Y)	EPR 12
Bearing limiting speed	4500 r/min
P60°	136 kN
P90°	81.4 kN
P120°	50.7 kN
P150°	46.3 kN
P180°	55.6 kN
Pa	13.8 kN
Mass pillow block	28.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g