

KOYO 32216JR tapered roller bearings

The online KOYO 32216JR tapered roller bearings parts store gives you immediate 140 mm Da access to a selection of more than 1.4 million 68.263 mm da 42.799 mm Ca new, used, remanufactured.

da	68.263 mm
Da	140 mm
Ca	42.799 mm
A1	88.9 mm
A2	126.603 mm
ba	30.163 mm
H	169.863 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	53.181 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	33.337 mm
Housing	FSAF 516
Bearing	1216 K

Adapter sleeve assembly	SNW 16×2.11/16
Stabilizing ring	2 x SR-1516
Labyrinth ring	2 x LOR 44
End plug (suffix Y)	EPR 8
Bearing limiting speed	6000 r/min
P60°	60.5 kN
P90°	36 kN
P120°	21.8 kN
P150°	19.6 kN
P180°	23.1 kN
Pa	6.23 kN
Mass pillow block	16.8 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	175.77 g