

KOYO 3582R/3525 tapered roller bearings

KOYO 3582R/3525 tapered roller bearings Engineering 2108 lb radial dynamic load capacity: Calculator , Manufacturing Service . Get 0.6250 in d Your Free.

| | |
|--------------------------------|-------------------------------|
| d | 0.6250 in |
| radial dynamic load capacity: | 2108 lb |
| D | 3.0000 in |
| radial static load capacity: | 1117 lb |
| B | 2.1250 in |
| seal type: | Single Lip Contact |
| overall height: | 1.0781 in |
| length through bore: | 0.9375 in |
| bore type: | Round |
| maximum operating temperature: | 200 °F |
| duty type: | Intermediate Duty |
| finish/coating: | Gray Painted |
| mounting type: | Two-Bolt Flange |
| bolt size: | 0.3750 in |
| housing material: | Cast Iron |
| maximum rpm: | 5000 RPM |
| locking device: | Set Screw |
| lubrication type: | Lubrication Fitting |
| expansion type: | Non-Expansion Bearing (Fixed) |
| series: | VF2S 100 |
| housing width: | 0.3750 in |
| application: | Browning – Standard |

| | |
|------------------------------|----------------------------|
| replacement bearing: | VS-110 |
| inner ring width: | 0.9375 in |
| manufacturer catalog number: | 767837 |
| bearing material: | 52100 Bearing Steel |
| manufacturer product page: | Click here |