

KOYO 3NC6002ST4 deep groove ball bearings

How do you find 88.9 mm da the KOYO 3NC6002ST4 deep groove ball bearings specification? Manufacturers Online Free check☐

da	88.9 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	222.25 mm
S	4.763 mm
ba	44.45 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
J1	60.325 mm
L	387.35 mm
N1	22.225 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	42.069 mm
Housing	FSAF 520
Bearing	22220 EK
Adapter sleeve assembly	SNW 20×3.1/2

Stabilizing ring	SR-20-17
Taconite seal	TER 103
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	900 r/min
P60°	119 kN
P90°	71.2 kN
P120°	44.5 kN
P150°	40 kN
P180°	48.9 kN
Pa	13.8 kN
Mass pillow block	28.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	181.44 g