

KOYO 3NCHAR934CA angular contact ball bearings

The 14 mm B online KOYO 3NCHAR934CA angular contact ball bearings parts store gives you immediate access to a selection of more than 1.4 35 mm d million new, used, remanufactured.

| | |
|---|-----------|
| d | 35 mm |
| D | 62 mm |
| B | 14 mm |
| rs min | 1 mm |
| Radial clearance class | C3 |
| Mass | 0.16 kg |
| Dynamic load, C | 16 kN |
| Static load, C ₀ | 10.3 kN |
| Fatigue limit load, C _u | 0.47 kN |
| f ₀ | 14.8 |
| N _{lim} (grease) | 6,800 rpm |
| Min operating temperature, T _{min} | -10 °C |
| Max operating temperature, T _{max} | 150 °C |
| Characteristic cage frequency, FTF | 0.42 Hz |
| Characteristic rolling element frequency, BSF | 5.95 Hz |
| Characteristic outer ring frequency, BPF ₀ | 4.6 Hz |
| Characteristic inner ring frequency, BRF ₀ | 6.4 Hz |
| da min | 40 mm |
| da max | 42 mm |

| | |
|------------------------|--|
| Da max | 57 mm |
| ra max | 1 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.152 |
| Product Group | B04270 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 3 ISO P6 |
| Material – Ball | Steel |
| Number of Bearings | 1 (Single) |
| Contact Angle | 0 Degree |
| Preload | None |
| Raceway Style | Not Applicable |
| Cage Material | Steel |
| Rolling Element | Ball Bearing |
| Enclosure Type | Contact Seal |
| Flush Ground | No |
| Inch – Metric | Metric |
| Other Features | Single Row Deep Groove C3 Clearance Prelubricant |
| Long Description | 35MM Bore; 62MM Outside Diameter; 14MM Width; 2 Seals Enclosure; ABEC 3 ISO P6 Precision; Steel Ba |
| UNSPSC | 31171502 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball Deep Groove |
| Outside Diameter | 2.441 Inch 62 Millimeter |

| | |
|-------|----------------------------|
| Bore | 1.378 Inch 35 Millimeter |
| Width | 0.551 Inch 14 Millimeter |