

# KOYO 46328A tapered roller bearings

170 Million used KOYO 46328A tapered roller bearings instantly searchable. Shop our large selection of parts based on brand, price, description, 25x62x17 Size (mm) and location. Order the with stock ... 62 Outer Diameter (mm)

Size (mm)	25x62x17
Bore Diameter (mm)	25
Outer Diameter (mm)	62
Width (mm)	17
d	25 mm
D	62 mm
B	17 mm
C	17 mm
Angle ( $\alpha$ )	30 °
a	4.1 mm
r min.	1.1 mm
r1 min.	0.6 mm
da min.	32 mm
Da max.	55 mm
ra max.	1 mm
Weight	0.245 Kg
Basic dynamic load rating (C)	26,4 kN
Basic static load rating (C0)	15,8 kN
(Grease) Lubrication Speed	10000 r/min
Configuration	Single Row
Enclosure	Open

Bore Type	Cylindrical Bore
Bore Size	25 mm
Outside Diameter	62 mm
Width	17 mm
Fillet Radius/Chamfer	1.1 mm
r1	0.6 mm
Dynamic Load Rating	26,400 N
Static Load Rating	15,800 N
Limiting Speed – Grease	10,000 rpm
Limiting Speed – Oil	14,000 rpm
da1 (min)	32 mm
da2 (min)	30 mm
Da1 (max)	55 mm
Da2 (max)	57 mm
ra (max)	1 mm
ra1 (max)	0.6 mm