

KOYO 46334 tapered roller bearings

KOYO 46334 tapered roller bearings, Units 35 Outer Diameter (mm) and Housings CAD models , Manufacturing 15x35x11 Size (mm) Service 15 Bore Diameter (mm) . Get Your Free.

| | |
|-------------------------------|--------------|
| Size (mm) | 15x35x11 |
| Bore Diameter (mm) | 15 |
| Outer Diameter (mm) | 35 |
| Width (mm) | 11 |
| d | 15 mm |
| D | 35 mm |
| B | 11 mm |
| C | 11 mm |
| rn | 0,5 mm |
| a | 2,06 mm |
| b | 1,35 mm |
| r min. | 0,6 mm |
| r0 max. | 0,4 mm |
| D1 | 33,17 mm |
| da min. | 19 mm |
| da max | 20,5 mm |
| Da max. | 31 mm |
| ra max. | 0,6 mm |
| Weight | 0,045 Kg |
| Basic dynamic load rating (C) | 7,65 kN |
| Basic static load rating (C0) | 3,75 kN |
| (Grease) Lubrication Speed | 20 000 r/min |

| | |
|-------------------------|--------------|
| (Oil) Lubrication Speed | 24 000 r/min |
| SRI | 3.01 |
| hidYobi | 6202N |
| LangID | 1 |
| ro | 0.4 |
| D_ | 35 |
| SREX | 0.03 |
| B_ | 11 |
| da min | 19 |
| hidTable | ecat_NSRDGB |
| Oil rpm | 24000 |
| SRE | 3.16 |
| mass | 0.045 |
| GRS rpm | 20000 |
| ra | 0.6 |
| SRIX | 0.015 |
| D_a | 31 |
| SRIN | 0 |
| C0 | 3.75 |
| fo | 13.2 |
| SREN | 0 |
| DE_ | 31.453 |
| Prod_Type3 | DGBB_SR_N_OT |
| DA_ | 5.953 |
| bomp | 0 |
| Z_ | 8 |
| yobi | 6202N |
| C_conv | 7650 |
| ALPHA_ | 0 |

| | |
|------|--------|
| SDM_ | 25.5 |
| r | 0.6 |
| KBRG | 6101 |
| SBRG | 2 |
| DI_ | 19.547 |