

KOYO 46790AR/46720 tapered roller bearings

With over 10170 Mounted Bearing Engineering Group full-service stores, our KOYO 46790AR/46720 tapered roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

| | |
|-------------------------|-----------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 55 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QMTU11J055SB |
| Locking Style | Eccentric |
| Weight | 21.0 lb |
| Housing Style | Take-Up |
| UPC Code | 0883450036627 |
| Dimension A | 2.38 in |
| Dimension C | 0.75 in |
| Dimension D | 5.25 in |
| Dimension E | 4.50 in |
| Dimension F | 1.19 in |
| Dimension G | 1.19 in |
| Dimension J | 3.50 in |
| Dimension L | 6.61 in |
| Dimension K | 1.13 in |
| Dimension M | 1.99 in |
| Dimension N | 3.26 in |
| Dimension P | 3.75 in |

| | |
|-------------------------------------|-----------|
| Dimension S | 0.810 in |
| C0 – Static Load | 31900 lb |
| C – Dynamic Load (Basic) | 31400 lb |
| e – Geometry Factor | 0.23 |
| Y1 – Geometry Factor | 2.95 |
| Y2 – Geometry Factor | 4.40 |
| Oil Lubrication – M/N Seal | 2200 rpm |
| Oil Lubrication – T Seal | 3800 rpm |
| Oil Lubrication – B/C/O Seal | 1600 rpm |
| Grease Lubrication – M/N Seal | 2200 rpm |
| Grease Lubrication – T Seal | 3200 rpm |
| Grease Lubrication – B/C/O Seal | 1600 rpm |
| Float | 0.050 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0016 |
| Eng Internal Radial Clearance – Max | 0.0026 |
| Pre Install Clearance Min | 0.040 mm |
| Pre Install Clearance Max | 0.065 mm |