

# KOYO 46790AR/46720 tapered roller bearings

With over 10170 Mounted Bearing Engineering Group full-service stores, our KOYO 46790AR/46720 tapered roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

Engineering Group	Mounted Bearing
Shaft Size	55 mm
Shaft Size Type	Metric
Full Timken Part Number	QMTU11J055SB
Locking Style	Eccentric
Weight	21.0 lb
Housing Style	Take-Up
UPC Code	0883450036627
Dimension A	2.38 in
Dimension C	0.75 in
Dimension D	5.25 in
Dimension E	4.50 in
Dimension F	1.19 in
Dimension G	1.19 in
Dimension J	3.50 in
Dimension L	6.61 in
Dimension K	1.13 in
Dimension M	1.99 in
Dimension N	3.26 in
Dimension P	3.75 in

Dimension S	0.810 in
C0 – Static Load	31900 lb
C – Dynamic Load (Basic)	31400 lb
e – Geometry Factor	0.23
Y1 – Geometry Factor	2.95
Y2 – Geometry Factor	4.40
Oil Lubrication – M/N Seal	2200 rpm
Oil Lubrication – T Seal	3800 rpm
Oil Lubrication – B/C/O Seal	1600 rpm
Grease Lubrication – M/N Seal	2200 rpm
Grease Lubrication – T Seal	3200 rpm
Grease Lubrication – B/C/O Seal	1600 rpm
Float	0.050 in
Shaft Tolerance	0.0015 in
Eng Internal Radial Clearance – Min	0.0016
Eng Internal Radial Clearance – Max	0.0026
Pre Install Clearance Min	0.040 mm
Pre Install Clearance Max	0.065 mm