

KOYO 47TS563932-2 tapered roller bearings

What 18 mm B is the best place to buy KOYO 47TS563932-2 tapered roller bearings online? 52 mm D Manufacturing Service . 25 mm d

d	25 mm
D	52 mm
B	18 mm
E	46.5 mm
F	31.5 mm
d1	34.5 mm
rs min	1 mm
r1s min	0.6 mm
Radial clearance class	C3
Mass (without HJ ring)	0.18 kg
Dynamic load, C	35 kN
Static load, C0	34.5 kN
Fatigue limit load, Cu	4.2 kN
Nlim (oil)	13,000 rpm
Nlim (grease)	11,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	5.01 Hz
Characteristic outer ring frequency, BPF0	5.25 Hz
Characteristic inner ring frequency, BRFI	7.75 Hz
da min	30 mm

da max	31 mm
dc min	37 mm
Da max	47 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.185
Product Group	B04144