

KOYO 6044ZZX deep groove ball bearings

High Quality KOYO 6044ZZX deep groove ball bearings. Competitive Pricing. Accept Small Order. 130x200x33 Size (mm) 200 Outer Diameter (mm) Easy and Fast Shipping.

Size (mm)	130x200x33
Bore Diameter (mm)	130
Outer Diameter (mm)	200
Width (mm)	33
d	130 mm
D	200 mm
B	33 mm
C	33 mm
r min.	2 mm
da min.	139 mm
da max	148 mm
Da max.	191 mm
ra max.	2 mm
Weight	3,16 Kg
Basic dynamic load rating (C)	106 kN
Basic static load rating (C0)	101 kN
Reference speed	1 900 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	3.16
EAN	4547359551303

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6026LLU/2A
Weight / LBS	6.97
Outer Race Width	1.299 Inch 33 Millimeter
Bore	5.118 Inch 130 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
bore diameter:	130 mm
static load capacity:	101000 N
outside diameter:	200 mm
precision rating:	ISO Class 0
overall width:	33 mm
finish/coating:	Uncoated

bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	33 mm
snap ring included:	Without Snap Ring
outer ring width:	33 mm
internal clearance:	CN
maximum rpm (grease):	1900 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	2 mm
dynamic load capacity:	106000 N
manufacturer product page:	Click here