

KOYO 6204-2RD deep groove ball bearings

Online shopping KOYO 6204-2RD deep groove ball bearings 42 mm D from a great selection at Store. ... 20 mm d Accessories. 12 mm B

d	20 mm
D	42 mm
B	12 mm
rs min	0.6 mm
Radial clearance class	C3
Mass	0.07 kg
Dynamic load, C	9.4 kN
Static load, C ₀	5.05 kN
Fatigue limit load, C _u	0.23 kN
f ₀	13.9
N _{lim} (grease)	11,000 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.76 Hz
Characteristic outer ring frequency, BPF ₀	3.59 Hz
Characteristic inner ring frequency, BPFI	5.41 Hz
da min	24 mm
da max	26 mm

Da max	38 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0692314653708
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	20MM Bore; 42MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing

Keyword String	Ball
Weight / LBS	0.152
Bore	0.787 Inch 20 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	1.654 Inch 42 Millimeter