

KOYO 66200R/66461 tapered roller bearings

100% Authentic. KOYO 66200R/66461 tapered roller bearings Highest Quality. Certified 225x105x49 Size (mm) 105 Outer Diameter (mm) Supplier.

Size (mm)	225x105x49
Bore Diameter (mm)	225
Outer Diameter (mm)	105
Width (mm)	49
d	105 mm
D	225 mm
B	49 mm
d1	145 mm
D1	189 mm
F	133 mm
r1,2 – min.	3 mm
r3,4 – min.	3 mm
s	3.4 mm
da – min.	119 mm
da – max.	129 mm
db – min.	148 mm
Da – max.	209.4 mm
ra – max.	2.5 mm
Basic dynamic load rating – C	500 kN
Basic static load rating – C0	500 kN
Fatigue load limit – Pu	57 kN
Reference speed	3200 r/min

Limiting speed	3800 r/min
Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	8.898
EAN	7316577062567
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity 1 Rib Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	105MM Bore; Straight Bore Profile; 225MM Outside Diameter; 49MM Width; Steel Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00

Noun	Bearing
Manufacturer Item Number	NJ 321 ECJ
Weight / LBS	19.599
Outside Diameter	8.858 Inch 225 Millimeter
Bore	4.134 Inch 105 Millimeter
Width	1.929 Inch 49 Millimeter
d1 ≈	145 mm
D1 ≈	189 mm
r1,2 min.	3 mm
r3,4 min.	3 mm
s max.	3.4 mm
da min.	119 mm
da max.	129 mm
db min.	148 mm
Da max.	209.4 mm
ra max.	2.5 mm
Basic dynamic load rating C	500 kN
Basic static load rating C0	500 kN
Fatigue load limit Pu	57 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	8.73 kg