## KOYO AX 5 30 47 needle roller bearings

KOYO AX 5 30 47 needle roller bearings Product Brochures , Manufacturing Service . Get Black Oxide finish/coating: Your Free. 5.1875 in d Four-Bolt Base mounting:

d 5.1875 in  finish/coating: Black Oxide  mounting: Four-Bolt Base  seal type: V-Ring  bearing type: Spherical Roller  radial dynamic load capacity: 228000 lb  bore type: Round  radial static load capacity: 275000 lb  housing construction: Split Pillow Block  maximum rpm: 1600 RPM		
mounting:  seal type:  bearing type:  radial dynamic load capacity:  bore type:  radial static load capacity:  275000 lb  housing construction:  Split Pillow Block  maximum rpm:  Four-Bolt Base  Four-Bolt Base  V-Ring  Spherical Roller  228000 lb  Sore type:  Round  75000 lb  1600 RPM	d	5.1875 in
seal type:  bearing type:  radial dynamic load capacity: 228000 lb  bore type:  radial static load capacity: 275000 lb  housing construction:  Split Pillow Block  maximum rpm:  1600 RPM	finish/coating:	Black Oxide
bearing type:  radial dynamic load capacity: 228000 lb  bore type:  radial static load capacity: 275000 lb  housing construction:  Split Pillow Block  maximum rpm:  1600 RPM	mounting:	Four-Bolt Base
radial dynamic load capacity: 228000 lb bore type: Round radial static load capacity: 275000 lb housing construction: Split Pillow Block maximum rpm: 1600 RPM	seal type:	V-Ring
bore type:  radial static load capacity: 275000 lb  housing construction: Split Pillow Block  maximum rpm: 1600 RPM	bearing type:	Spherical Roller
radial static load capacity: 275000 lb housing construction: Split Pillow Block maximum rpm: 1600 RPM	radial dynamic load capacity:	228000 lb
housing construction: Split Pillow Block maximum rpm: 1600 RPM	bore type:	Round
maximum rpm: 1600 RPM	radial static load capacity:	275000 lb
'	housing construction:	Split Pillow Block
hase to hore centerline: 6 3125 in	maximum rpm:	1600 RPM
base to bore certer time.	base to bore centerline:	6.3125 in
lubrication type: Lubrication Fitting	lubrication type:	Lubrication Fitting
duty type: Standard Duty	duty type:	Standard Duty
end type: Open	end type:	0pen
housing material: Cast Iron	housing material:	Cast Iron
series: 530	series:	530
locking device: Adapter Mount	locking device:	Adapter Mount
UL, AFBMA, AGMA, ASMMA, ASTM standards met:  A48 Class 30, BSA, CMA, MPTA, PTDA	standards met:	A48 Class 30, BSA, CMA, MPTA,
D 16-3/4 to 18-1/4 in	D	16-3/4 to 18-1/4 in
replacement bearing: 22200K	replacement bearing:	22200K

expansion type:	Non-Expansion Bearing (Fixed)
manufacturer catalog number:	042438