

KOYO DC4920AVW cylindrical roller bearings

The online KOYO DC4920AVW cylindrical roller bearings 75 Outer Diameter (mm) parts store gives you immediate access to a selection of more than 1.4 25x75x28 Size (mm) million new, used, remanufactured.

Size (mm)	25x75x28
Bore Diameter (mm)	25
Outer Diameter (mm)	75
Width (mm)	28
d	25 mm
D	75 mm
H	6.8 mm
d1	40.5 mm
D1	49 mm
H1	19 mm
r1,2 – min.	0.3 mm
r3,4 – min.	0.8 mm
a	84 mm
J	58 mm
da – min.	32 mm
Da – max.	49 mm
ra – max.	0.6 mm
Basic dynamic load rating – C	27.6 kN
Basic static load rating – C0	55 kN
Fatigue load limit – Pu	2 kN
Limiting speed	3400 r/min

Preload	1920 N
Frictional moment	0.4 N·m
Static Axial rigidity	770 N/micron
Mass bearing	0.72 kg
Required attachment bolt size	M6
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	7316572024157
Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 5 ISO P5
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	60 Degree
Raceway Style	Not Applicable
Cage Material	Polyamide
Rolling Element	Ball Bearing
Enclosure Type	Contact Seal
Flush Ground	No
Inch – Metric	Metric
Other Features	Double Row Angular Contact Thrust Bearing Double Direction
Long Description	25MM Bore; 75MM Outside Diameter; 28MM Width; 2 Seals Enclosure; ABEC 5 ISO P5 Precision; Steel Ba
UNSPSC	31171531

Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Ball Angular Contact
Manufacturer Item Number	BEAM 025075-2RS/PE
Weight / LBS	0.062
Width	1.102 Inch 28 Millimeter
Bore	0.984 Inch 25 Millimeter
Outside Diameter	2.953 Inch 75 Millimeter