

# KOYO EE239170/239225A tapered roller bearings

High Quality KOYO EE239170/239225A tapered roller bearings. Competitive Pricing. Accept Small Order. Easy and 0.0 Inventory Fast Shipping.

|                           |                                    |
|---------------------------|------------------------------------|
| Inventory                 | 0.0                                |
| Manufacturer Name         | TIMKEN                             |
| Minimum Buy Quantity      | N/A                                |
| Weight                    | 6.356                              |
| EAN                       | 0883450145442                      |
| Product Group             | M06288                             |
| Number of Mounting Holes  | 2                                  |
| Mounting Method           | V Lock                             |
| Housing Style             | 2 Bolt Pillow Block                |
| Rolling Element           | Spherical Roller Bearing           |
| Housing Material          | Cast Steel                         |
| Expansion / Non-expansion | Expansion                          |
| Mounting Bolts            | 5/8 Inch                           |
| Relubricatable            | Yes                                |
| Insert Part Number        | 22211                              |
| Seals                     | Triple Lip Nitrile Rubber          |
| Housing Configuration     | 1 Piece Solid                      |
| Inch – Metric             | Metric                             |
| Other Features            | Double Row   Single Nut   SN Style |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 50MM Bore; 70MM Base to Center Height; V Lock Mount; Spherical Roller Bearing; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Weight / LBS                  | 14  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| B                             | 2.756 Inch   70 Millimeter  |
| D                             | 3.14 Inch   79.756 Millimeter   |
| Bolt Spacing Minimum          | 6.5 Inch   165.1Millimeter  |
| Bolt Spacing Maximum          | 8.7 Inch   220.98Millimeter   |
| d                             | 1.969 Inch   50 Millimeter  |
| Nominal Bolt Center to Center | 7.6 Inch   193 Millimeter   |