

# KOYO HI-CAP TR080802DYA1LFT tapered roller bearings

Offer High Quality Brand KOYO HI-CAP TR080802DYA1LFT tapered roller bearings 0.0 Inventory .Contact Us Online to Get Best Quote. N/A Minimum Buy Quantity

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 19.07  |
| EAN                       | 0662327110390  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 7/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | B22455EL   |
| Seals                     | Spring Loaded Lip  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Collar   Closed End   Extended Inner Race   With Set Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 3-7/16" Bore; 3-3/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | PB22455EEC  |
| Manufacturer Internal Number  | 5811039   |
| Weight / LBS                  | 42  |
| Nominal Bolt Center to Center | 10 Inch   254 Millimeter  |
| D                             | 4.375 Inch   111.13 Millimeter  |
| B                             | 3.75 Inch   95.25 Millimeter  |
| Actual Bolt Center to Center  | 10 Inch   254Millimeter   |
| d                             | 3.438 Inch   87.325 Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |