## KOYO KDX110 angular contact ball bearings

170 Million used KOYO KDX110 angular contact ball bearings instantly TIMKEN Manufacturer Name searchable. Shop our large selection of parts based on brand, 0.0 Inventory price, description, and location. Order the with stock ...

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 19.522   |
| EAN                       | 0883450094078  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Triple Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 4 Bolt Pillow Block; 3-7/16"<br>Bore; 4" Base to Center Height;<br>Eccentric Collar Mount; Spher |

| UNSPSC                           | 31171511                       |
|----------------------------------|--------------------------------|
| Harmonized Tariff Code           | 8483.20.40.80                  |
| Noun                             | Bearing                        |
| Keyword String                   | Pillow Block                   |
| Manufacturer Item Number         | QMPX18J307SEN                  |
| Weight / LBS                     | 49                             |
| Bolt Spacing Maximum             | 12.19 Inch   309.626Millimeter |
| d                                | 3.438 Inch   87.325 Millimeter |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter           |
| D                                | 4.03 Inch   102.362 Millimeter |
| Bolt Spacing Minimum             | 10.81 Inch   274.574Millimeter |
| В                                | 4 Inch   101.6 Millimeter      |
| Nominal Bolt Center to<br>Center | 11.5 Inch   292.1 Millimeter   |