

# KOYO LM283649/LM283610 tapered roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you 0.0 Inventory with all your KOYO LM283649/LM283610 tapered roller bearings needs – including routine maintenance, major repairs, warranty N/A Minimum Buy Quantity service, and equipment inspections.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	74 lb
EAN	0013992041111
Product Group	B04144
Number of Mounting Holes	2
Mounting Method	Clamp Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	24 Millimeter
Relubricatable	Yes
Insert Part Number	LSE400BX
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Single Row   Light Duty   With Support   Wide Inner Ring
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Weight / LBS	62.37
Bolt Spacing Minimum	0 Inch   0Millimeter
Nominal Bolt Center to Center	13.9 Inch   354 Millimeter
Actual Bolt Center to Center	13.9 Inch   354Millimeter
d	4 Inch   101.6 Millimeter
D	3.346 Inch   85 Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
B	4.921 Inch   125 Millimeter
Shaft Size	4 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Expansion Type
Support Type	Two-Bolt Plummer Block
Series Type	Light Series
Pillow/Plummer Block Style	Split Cylindrical Housed Unit – Standard
Bolt Size	2 x M24
Dimension H	4.921 in
Dimension H1	2.0 in
Dimension H2	10.7 in
Dimension J	13.9 in
Dimension L	16.5 in
Dimension M	4.0 in
Housing Width	5.3 in
Cr – Dynamic Load Rating	64745 lbf
Cor – Static Load Rating	82280 lbf

Maximum Speed	2340 rpm
Note	This product line was formerly known as "Revolvo"