

KOYO MJH-881 needle roller bearings

Request A Quote For 95x170x32 Size (mm) Your Special KOYO MJH-881 needle roller bearings Needs Today! Free Quotes. ISO 9001 certified.

Size (mm)	95x170x32
Bore Diameter (mm)	95
Outer Diameter (mm)	170
Width (mm)	32
d	95 mm
D	170 mm
B	32 mm
C	32 mm
r min.	2,1 mm
da min.	106 mm
da max	114 mm
Da max.	159 mm
ra max.	2 mm
Weight	2,64 Kg
Basic dynamic load rating (C)	109 kN
Basic static load rating (C0)	82 kN
(Grease) Lubrication Speed	3 800 r/min
(Oil) Lubrication Speed	4 500 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.58

EAN	0029176015779
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	95MM Bore; 170MM Outside Diameter; 32MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6219
Weight / LBS	2.605
Bore	3.74 Inch 95 Millimeter
Outer Race Width	1.26 Inch 32 Millimeter
Outside Diameter	6.693 Inch 170 Millimeter
bore diameter:	95 mm
internal clearance:	C3
outside diameter:	170 mm
dynamic load capacity:	109000 N
overall width:	32 mm
precision rating:	ABEC1, P0

bore type:	Round
finish/coating:	Uncoated
closure type:	Open
cage material:	Steel Cage
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	4500 rpm
snap ring included:	Without Snap Ring
SRI	12.32
hidYobi	6219
LangID	1
D_	170
SREX	0.04
B_	32
da min	106
hidTable	ecat_NSRDGB
Oil rpm	4500
SRE	12.32
mass	2.64
GRS rpm	3800
ra	2
SRIX	0.04
D_a	159
SRIN	-0.04
C0	82
fo	14.4
SREN	-0.04
DE_	156.312
Prod_Type3	DGBB_SR_OT
DA_	23.812

bomp	0
Z_	10
yobi	6219
C_conv	109000
ALPHA_	0
SDM_	132.5
r	2.1
KBRG	6101
SBRG	2
DI_	108.688