

KOYO NA2120 needle roller bearings

100% 20x52x15 Size (mm) 20 Bore Diameter (mm) Authentic. 52 Outer Diameter (mm) KOYO NA2120 needle roller bearings Highest Quality. Certified Supplier.

Size (mm)	20x52x15
Bore Diameter (mm)	20
Outer Diameter (mm)	52
Width (mm)	15
d	20 mm
D	52 mm
B	15 mm
C	15 mm
rn	0,5 mm
a	2,46 mm
b	1,35 mm
f	1,12 mm
r min.	1,1 mm
r θ max.	0,4 mm
D1	49,73 mm
D2	57,9 mm
da min.	26,5 mm
da max	28 mm
Da max.	45,5 mm
ra max.	1 mm
Weight	0,145 Kg
Basic dynamic load rating (C)	15,9 kN

Basic static load rating (C0)	7,9 kN
(Grease) Lubrication Speed	14 000 r/min
(Oil) Lubrication Speed	17 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.07
EAN	0029176034978
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6304NR
Weight / LBS	0.147
Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter

Bore	0.787 Inch 20 Millimeter
SRI	4.81
hidYobi	6304NR
LangID	1
ro	0.4
D_	52
SREX	0.04
B_	15
da min	26.5
hidTable	ecat_NSRDGB
Oil rpm	17000
SRE	5
Cy	3.3
mass	0.145
GRS rpm	14000
ra	1
SRIX	0.02
D_a	45.5
SRIN	0
C0	7.9
fo	12.4
SREN	0
DE_	45.525
Prod_Type3	DGBB_SR_NR_OT
DA_	9.525
bomp	0
Z_	7
yobi	6304NR
Dx	58.5

C_conv	15900
ALPHA_	0
SDM_	36
r	1.1
KBRG	6101
SBRG	3
DI_	26.475