

# KOYO NF206 cylindrical roller bearings

What are the dimensions of a KOYO NF206 cylindrical roller bearings? 0.0 Inventory Manufacturing Service . Get Your Free, ABB MOTORS AND MECHANICAL INC Manufacturer Name Instant Quote

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC               |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 36.774                                      |
| EAN                       | 0782475021116                               |
| Product Group             | M06288                                      |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Adapter Sleeve                              |
| Housing Style             | 4 Bolt Pillow Block                         |
| Rolling Element           | Spherical Roller Bearing                    |
| Housing Material          | Cast Iron                                   |
| Expansion / Non-expansion | Non-expansion                               |
| Mounting Bolts            | 3/4 Inch                                    |
| Relubricatable            | Yes   |
| Insert Part Number        | BRG22220KC3                                 |
| Seals                     | Triple Tect                                 |
| Housing Configuration     | 2 Piece Split                               |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Open End   Corrosion Resistant |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 3-1/2" Bore; 4-1/2" Base to Center Height; Adapter Sleeve Mount; Sphe |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | P4B520-USAF-308TT USAF   |
| Manufacturer Internal Number  | 041871   |
| Weight / LBS                  | 61.8   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| D                             | 6.781 Inch   172.237 Millimeter  |
| B                             | 4.5 Inch   114.3 Millimeter  |
| Bolt Spacing Minimum          | 11.625 Inch   295.275Millimeter  |
| Bolt Spacing Maximum          | 13.125 Inch   333.375Millimeter  |
| d                             | 3.5 Inch   88.9 Millimeter   |
| Nominal Bolt Center to Center | 12.1 Inch   308.5 Millimeter   |