KOYO NJ308R cylindrical roller bearings

Manufacturers of all are represented in our partial 655 Series list of clients. Contact Gary for a complete KOYO NJ308R cylindrical roller bearings list of clients and projects.

| Series | 655 |
|--------------------------------------|---------------|
| Cone Part Number | 655 |
| Cup Part Number | 652-B |
| Design Units | Imperial |
| Bearing Weight | 8.2 lb |
| Cage Type | Stamped Steel |
| d | 2.7500 in |
| D | 6.0000 in |
| D1 — Flange Outer Diameter | 6.2772 in |
| B — Cone Width | 1.6250 in |
| C — Cup Width | 1.2500 in |
| C1 — Cup Flange Width | 0.2812 in |
| T1 — Bearing Width | 1.625 in |
| T — Bearing Width to Flange | 0.6562 in |
| R — Cone Backface To Clear Radius1 | 0.14 in |
| r — Cup Backface To Clear Radius2 | 0.130 in |
| da — Cone Frontface Backing Diameter | 3.23 in |
| db — Cone Backface Backing Diameter | 3.46 in |
| Da — Cup Frontface Backing Diameter | 5.57 in |
| Ab — Cage-Cone Frontface Clearance | 0.1 in |
| Aa — Cage-Cone Backface Clearance | 0.17 in |
| a — Effective Center Location3 | -0.31 in |

| C90 — Dynamic Radial Rating (90 million revolutions)4 | 14400 lbf |
|--|-----------|
| C1 — Dynamic Radial Rating (1 million revolutions)5 | 55500 lbf |
| CO — Static Radial Rating | 75300 lbf |
| Ca90 — Dynamic Thrust Rating (90 million revolutions)6 | 10100 lbf |
| K - Factor7 | 1.43 |
| e - ISO Factor8 | 0.41 |
| Y - ISO Factor9 | 1.47 |
| G1 — Heat Generation Factor (Roller-Raceway)10 | 137 |
| G2 — Heat Generation Factor (Rib-Roller End) | 27.3 |
| Cg — Geometry Factor11 | 0.0919 |