

KOYO R25/10A needle roller bearings

KOYO R25/10A needle roller bearings Manufacturers 170x95x32 Size (mm) , 170 Bore Diameter (mm) Online Wholesale Suppliers !

| | |
|-------------------------------|------------|
| Size (mm) | 170x95x32 |
| Bore Diameter (mm) | 170 |
| Outer Diameter (mm) | 95 |
| Width (mm) | 32 |
| d | 95 mm |
| D | 170 mm |
| B | 32 mm |
| d1 | 120 mm |
| D1 | 148.15 mm |
| F | 112.5 mm |
| r1,2 – min. | 2.1 mm |
| r3,4 – min. | 2.1 mm |
| s | 1.7 mm |
| da – min. | 107 mm |
| da – max. | 110 mm |
| db – min. | 123 mm |
| Da – max. | 157.8 mm |
| ra – max. | 2 mm |
| Basic dynamic load rating – C | 255 kN |
| Basic static load rating – C0 | 265 kN |
| Fatigue load limit – Pu | 32.5 kN |
| Reference speed | 4300 r/min |

| | |
|-----------------------------|------------|
| Limiting speed | 7000 r/min |
| Calculation factor – kr | 0.23 |
| d1 ≈ | 120 mm |
| D1 ≈ | 148.15 mm |
| r1,2 min. | 2.1 mm |
| r3,4 min. | 2.1 mm |
| s max. | 1.7 mm |
| da min. | 107 mm |
| da max. | 110 mm |
| db min. | 123 mm |
| Da max. | 157.8 mm |
| ra max. | 2 mm |
| Basic dynamic load rating C | 255 kN |
| Basic static load rating C0 | 265 kN |
| Fatigue load limit Pu | 32.5 kN |
| Calculation factor kr | 0.23 |
| Limiting value e | 0.2 |
| Axial load factor Y | 0.6 |
| Mass bearing | 3.16 kg |
| Angle ring | HJ 219 EC |