

KOYO RS374231 needle roller bearings

Question KOYO RS374231 needle roller bearings ? Find what you need faster by 170 mm da entering your information .

da	170 mm
db	188.912 mm
dc	163.512 mm
Da	309.999 mm
Ca	119.812 mm
A1	171.45 mm
A2	309.563 mm
S	4.763 mm
ba	88.106 mm
H	360.363 mm
H1	179.4 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	54.769 mm
Housing	SAW 234

Bearing	23234 CC/W33
Lock nut	AN 34
Lock washer	W 34
Stabilizing ring	SR-34-0
Taconite seal (db shaft position)	TER 161
Taconite seal (dc shaft position)	TER 148
End plug (suffix Y)	EPR 19
Max. speed for Taconite seal	410 r/min
P60°	234 kN
P90°	140 kN
P120°	85.9 kN
P150°	77 kN
P180°	92.5 kN
Pa	56 kN
Mass pillow block	135 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g