

KOYO SVWML 6010 ZZST deep groove ball bearings

With over 10170 full-service stores, our KOYO SVWML 6010 ZZST deep groove ball bearings inventory is extensive and our parts are priced right. within 24 440x240x190 Size (mm) hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

Size (mm)	440x240x190
Bore Diameter (mm)	440
Outer Diameter (mm)	240
Width (mm)	190
d1	240 mm
D	440 mm
B1	190 mm
d2	314 mm
d3	310 mm
D1	394 mm
B	144 mm
B2	34 mm
B5	46 mm
s1	26.4 mm
r1,2 – min.	4 mm
da – max.	341 mm
db – min.	276 mm
Da – min.	371 mm
Da – max.	423 mm
Ba – min.	11 mm

Ca – min.	4.1 mm
ra – max.	3 mm
Basic dynamic load rating – C	2650 kN
Basic static load rating – C0	4050 kN
Fatigue load limit – Pu	325 kN
Reference speed	1100 r/min
Limiting speed	1500 r/min
Factor – k1	0.115
Factor – k2	0.096
d2 ≈	314 mm
D1 ≈	394 mm
s1 max.	26.4 mm
r1,2 min.	4 mm
da max.	341 mm
db min.	276 mm
Da min.	371 mm
Da max.	423 mm
Ba min.	11 mm
Ca min.	4.1 mm
ra max.	3 mm
Basic dynamic load rating C	2650 kN
Basic static load rating C0	4050 kN
Fatigue load limit Pu	325 kN
Misalignment factor k1	0.115
Operating clearance factor k2	0.096
Mass bearing + sleeve	105 kg