

KOYO UCFC206 bearing units

KOYO UCFC206 bearing units 125 mm D SEARCH – Whether 70 mm d it's agriculture or construction equipment your working on, Has the 24 mm B you need.

d	70 mm
D	125 mm
B	24 mm
a	53 mm
Contact angle α	40 °
rs min	1.5 mm
r1s min	1 mm
Mass	1.25 kg
Dynamic load, C	69 kN
Static load, C0	58 kN
Fatigue limit load, Cu	2.65 kN
Nlim (oil)	6,500 rpm
Nlim (grease)	4,900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	78.5 mm
db min	75.5 mm
Da max	116.5 mm
Db max	119.5 mm
r1a max	1 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN

Minimum Buy Quantity	N/A
Weight / Kilogram	1.25
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	70MM Bore; 125MM Outside Diameter; 24MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Width	0.945 Inch 24 Millimeter
Bore	2.756 Inch 70 Millimeter
Outside Diameter	4.921 Inch 125 Millimeter